

ANKE-FXMC SERIES SQUARE BOX PULSE DUST COLLECTOR PERFORMANCE PARAMETERS							
Model&Specs		Filter Bag Size (mm)	Filtering Area (m ²)	Capacity (m ³ /h)	Pulse Valves	OVERALL DIMENSION (mm)	Referenced Weight (t)
AK04-FXMC-168	I	φ120*3000	190	11400-22800	14	2760*2410*8230	9.4
	II	φ120*4000	252	15120-30240		2760*2410*9230	103
AK04-FXMC-336	I	φ120*3000	380	22800-45600	28	5520*2410*8230	17.9
	II	φ120*4000	504	30240-60480		5520*2410*9230	19.4
AK04-FXMC-504	I	φ120*3000	570	34200-68400	42	8280*2410*8230	25.3
	II	φ120*4000	766	45360-90720		8280*2410*9230	27.6
AK04-FXMC-672	I	φ120*3000	760	45600-91200	56	11040*2410*8230	31.7
	II	φ120*4000	1008	60480-120960		11040*2410*9230	34.6
AK04-FXMC-840	I	φ120*3000	950	57000-114000	70	13800*2410*8230	39.7
	II	φ120*4000	1260	75600-151200		13800*2410*9230	43.2

NOTE: (1) Filtering Speed:1.0-2.0m/min (2) Equipment Resistance: ≤ 1700pa (3) Collector Leakage: ≤ 2%; (4) Filter pressure:4000pa
(5) Output Dust Concentration: 50mg/Nm³ (6) Air source pressure:0.4-0.6Mpa (7)Air Consumed:Valve/Time 0.1-0.15m³